



| REV. | REVISION RECORD | DATE | REV. | REVISION RECORD | DATE |
|------|-----------------|------|------|-----------------|------|
| A | | | C | | |
| B | | | D | | |

| | | | | | | | |
|----------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--------|---------------|
| NAME | 1018 葉管 | MATERIAL | PP | SCALE | 2/1 | ANGLE: | $\pm 1^\circ$ |
| DRAWING NO. | HY P008 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV.: | A |
| TOLERANCE OF PIN PITCH ± 0.20 | |  | |  信詠塑膠工業股份有限公司 HSIN YUNG PLASTIC INDUSTRIAL CO.,LTD. TEL:886-2-29953711 FAX:886-2-29990010 信詠塑膠電子廠 HSIN YUNG PLASTIC ELECTRONICS FACTORY TEL:0769-6632011 FAX:0769-6635843 | | | |
| PIN TENSION LOAD 1.0kg MIN | | UL REC.:94V-0 | | | | | |
| TOLERANCES: $0 < L \leq 4: \pm 0.1$ $4 < L \leq 16: \pm 0.2$ $16 < L \leq 63: \pm 0.3$ | | | | | | | |